

SeparatoR® FR

UL CLASS A APPROVED FOR MECHANICALLY FASTENED SINGLE PLY SYSTEMS OVER WOOD DECKS



LABOR SAVINGS

Easy cutting, handling and installation Extremely lightweight at 11.5 pounds per 4' x 8' board

MORE BOARDS PER TRUCK

Lower freight costs Less fuel surcharge Less unloading/loading time

LOW DUST ENVIRONMENT — NO SILICA EXPOSURE MOISTURE AND MOLD RESISTANCE HIGH R-VALUE (2.9)

UL CLASS A APPROVAL WITH MECHANICALLY FASTENED TPO					
Deck	Incline	Insulation*	Membrane		
C-15/32	3/4	SeparatoR FR	JM TPO		
C-15/32	1/2	SeparatoR FR	JM TPO FB		

UL CLASS A APPROVAL WITH MECHANICALLY FASTENED PVC					
Deck	Incline	Insulation*	Membrane		
C-15/32	2	SeparatoR FR	JM PVC		
C-15/32	2	SeparatoR FR	JM PVC SD Plus		

UL CLASS A APPROVAL WITH MECHANICALLY FASTENED EPDM					
Deck	Incline	Insulation*	Membrane		
C-15/32	1/2	SeparatoR FR	JM EPDM R		

^{*}All joints staggered a minimum of 6" from the plywood joints

